(19) World Intellectual Property **Organization**

International Bureau



553653) CORRO CUMBION IN CORROR CORRO COMO COMO CORRO CORRO

(43) International Publication Date 21 October 2004 (21.10.2004)

(10) International Publication Number WO 2004/089850 A2

- (51) International Patent Classification7: 41/50, 35/52, C22C 26/00
- C04B 35/573,
- (21) International Application Number:

PCT/EP2004/050367

- (22) International Filing Date: 26 March 2004 (26.03.2004)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0301117-8

14 April 2003 (14.04.2003) SE

- (71) Applicant (for all designated States except US): SKELE-TON TECHNOLOGIES AG [CH/CH]; Zugerstrasse 72, CH-6340 Baar (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): SVENDSEN. Lena [SE/SE]; Zinkens väg 65, S-117 41 Stockholm (SE). ZHENG, Jie [SE/SE]; Hagalundsgatan 14, S-169 63 Solna (SE). MEURLING, Fredrik [SE/SE]; Wollmaryxkullsgatan 11, S-118 50 Stockholm (SE). ROSTVALL, Tomas —/SE]; Selmedalsringen 8, S-129 36 Hägersten (SE).
- (74) Agents: ALBIHNS STOCKHOLM AB et al.; P.O. Box 5581, Linnégatan 2, S-114 85 Stockholm (SE).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD FOR MANUFACTURING A DIAMOND COMPOSITE

(57) Abstract: The present invention relates to a method for manufacturing a diamond composite, comprising the steps of: a) mixing diamonds with additives, the mixture comprising at least 50 wt% and less than 95 wt% of diamonds and more than 5 wt% additives; b) forming a work piece from the mixture using a pressure of at least 100 Mpa; c) heating the formed work piece to at least 300°C for removing possible water and wholly or partially removing additives; d) heating the work piece and controlling the heating temperature and heatin time so that a certain desired amount of graphite is created by graphitization of diamonds, wherein the amount of graphite created by graphitization is 3-50 wt% of the amount of diamond; e) infiltrating silicon or silicon alloy into the work piece, the infiltration of silicon or silicon alloy being performed at a temperature below 1900°C and a pressure less than 50 bars; and f) heating the infiltrated work piece to form silicon carbide, or other carbides, (and silicides), thereby creating a final diamond composite.

